

CREEL



3111 Air-Blow Label Applicator **Item: 3111**

The Label-Aire Model 3111 label applicator makes labeling easier and faster... making you more profitable.

The Model 3111 Air-Blow label applicator delivers on its promise of speed, accuracy, and ease of use. That translates into lower operating costs and increased productivity for your business.

Advanced features include Velocity Compensation for improved label placement accuracy. Speeds of up to 1,500 inches (3,810 cm) of web per minute and Zero Downtime Labeling allow your production to continue without costly interruptions. Label queuing and missing label compensation virtually eliminate unlabeled products.

Put this air-blow pressure-sensitive technology to work for you all day, every day. The Model 3111 Air-Blow labeler is built to meticulous quality standards and designed to withstand the most intense operation.

CREEL

- **Automatic setup** with multiple programmable label pages for easy changeovers to different label sizes.
- **Stepper motor drive** for precise starting / stopping, increased reliability, wider range speed variability, and lower maintenance.
- **R3 digital display** offers selection of five languages (English, French, German, Italian, Spanish), domestic or CE (European) configurations, standard/metric unit display and detailed alarm messages. Can rotate 360°.
- **Velocity compensation** for improved label placement accuracy.
- **Quick-Action collapsible** rewind allows easy removal of scrap liner.
- **Optional smart powered rewind** for improved label accuracy and dynamic web tension control.
- **Easily adapts** to tamp-blow or wipe-on use.

Specs

- **Dimensions:** Height: 26.47" (672.3 mm), Length: 33.4" (849.3 mm), Width: 21.84" (554.6 mm)
- **Weight:** 140 lbs. (63.5 kg)
- **Standard Label Dimensions:** Min .75" x .75" (19mm x 19mm), Max 3" x 3" (76mm x 76mm)
- **Label Packaging:** 12" (305 mm) O.D. rolls std. on 3" (76 mm) I.D. cores, up to 16" (406 mm) or 20" (508 mm) roll with optional 16" (406 mm) non-powered rewind or 20" (508 mm) powered unwind
- **Dispense Speed:** Up to 1,000" (3,810 cm) of web per minute (standard), up to 1,500" (5,080 cm) of web per minute with smart powered unwind
- **Label Dispense Accuracy:** +/- 1/32" (.8 mm)
- **Electrical:** 115 Volts AC 60 Hz 3 Amps., 220 Volts AC 50 Hz optional
- **Air:** 4 cfm at 90 psi to 110 psi for most applications